



▲ALL TERMINALS MUST BE  
COPLANAR WITHIN 0.10  
[.004]  
TOTAL

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 50mA @ 50 VDC
- ▲5. OPERATING FORCE: 160±50 gF
6. TRAVEL: 0.25mm +0.2/-0.1
7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL LIFE: 1,000,000 CYCLES
- ▲9. CONTACT MATERIAL: SILVER
- ▲10. PACKAGE: TAPE AND REEL, 1200 PIECES PER REEL
11. ▲DENOTES CRITICAL PARAMETER
12. 2002/95/EC (ROHS) COMPLIANT
- ▲13. STAINLESS STEEL DOME

**E-SWITCH®**

B	16448	FIXED NOTE #8	9/12/06	BO
A	16411	RELEASED FOR PRODUCTION	9/5/06	BO
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3301AF160QGSSDOME				
SCALE	DATE	DR	DWG	REV
4:1	9/5/2006	BO	P010577	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED