

- Guaranteed compatibility with recommended Tripp Lite cabling, including the N820-, N821-, N844- and N858 Series cables
- 8-fiber MTP ports are Polarity B, optimized for parallel optics and Base-8 Connectivity

## 40 GB to 10 GB Breakout Cassette, (x3) 8-Fiber OM4 MTP/MPO (Male with Pins) to (x12) LC Duplex, Type-B Polarity

MODEL NUMBER: **N482-3M8-LC12**



### Description

The N482-3M8-LC12 40 GB to 10 GB Breakout Cassette works in tandem with Tripp Lite's [N482-01U](#) or [N482-02U](#) chassis to connect 12 LC duplex fiber cables with three 8-fiber MTP/MPO connections in high-density network applications. It's compatible with recommended Tripp Lite cabling, including the N820-, N821-, N844- and N858 Series. Its 8-fiber MTP ports are Polarity B, optimized for parallel optics and Base-8 connectivity.

The cassette's modular design installs easily in the [N482-01U](#) and [N482-02U](#) chassis with no tools required. Just insert the cassette into the chassis, and snap in its retention clips to secure it. Plug LC patch cables, such as Tripp Lite's [N820-01M-T](#) cables, into the cassette using the cable's convenient push/pull tabs. Up to five N482-3M8-LC12 cassettes fit in the [N482-01U](#) 1U enclosure panel, and 14 cassettes fit in the [N482-02U](#) 2U chassis. Dust tabs protect unused ports from potential damage.

The N482-3M8-LC12 complies with IEEE 802.3ae (10 GbE) and ANSI T11.2 (Fibre Channel) requirements. Supports 40 GbE internally using OM4 fiber optic cable. Ideal for QSFP fabric switches that use eight out of 12 available MTP fibers for four-lane parallel optics to 40 GB, allowing all 12 LC duplex cassette ports to be used. Maximum insertion loss of 0.35 dB falls well under the IEEE 802.3ae maximum channel loss specification of <25 dB. This cassette also supports devices of varying speeds, including 10 GB and 40 GB network equipment.

### Features

#### Elegant, Simple Solution for 40 GB to 10 GB LC Cable Connections

- High-density fiber cassette for use with Tripp Lite [N482-01U](#) and [N482-02U](#) fiber enclosure panels
- Connect up to 12 LC duplex fiber cables with three 8-fiber MTP/MPO connections
- Ideal for use with QSFP fabric switches to support 4 lanes parallel to 40 GB
- Supports 40 GbE internally using OM4 fiber optic cable

### Highlights

- For use with Tripp Lite [N482-01U](#) or [N482-02U](#) chassis
- Simple installation with no tools required
- Factory-terminated OM4 connectors
- Supports 40 GbE internally using OM4 fiber optic cable
- Designed for use with recommended Tripp Lite cabling

### System Requirements

- QSFP switches that use 8-fiber per port to support 4 x LC 10 GB breakout
- Guaranteed compatibility with recommended Tripp Lite cabling, including the N820-, N821-, N844- and N858 Series cables
- 8-fiber MTP ports are Polarity B, optimized for parallel optics and Base-8 Connectivity

### Package Includes

- N482-3M8-LC12 40 GB to 10 GB Breakout Cassette
- Quick Start Guide



- 8-fiber MTP ports are Polarity B, optimized for parallel optics and Base-8 connectivity

#### Designed Specifically for Use with Tripp Lite Cabling

- Guaranteed compatibility with recommended Tripp Lite cables, including N820-, N821-, N844- and N858 Series

#### Simple Fiber Installations Save Time and Money

- Easy installation with no tools required
- Install up to 14 cassettes in [N482-02U](#) 2U chassis
- Install up to 5 cassettes in [N482-01U](#) 1U chassis

#### Easy to Modify, Upgrade or Expand Fiber Infrastructure by Adding or Swapping Cassettes

- Complies with IEEE 802.3ae (10 GbE) and ANSI T11.2 (Fibre Channel) requirements
- 0.35 dB maximum insertion loss falls under IEEE 802.3ae maximum channel loss spec of <25 dB
- Supports devices of varying speeds, including 10 GB and 40 GB network equipment

#### Premium Construction for Optimal Performance

- Factory-terminated connectors reduce time and labor
- Dust caps protect unused ports

## Specifications

CONNECTIONS	
Ports	12
Side A - Connector 1	(3) 8-STRAND MTP (MALE)
Side B - Connector 1	(12) LC DUPLEX (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.triplite.com/products/product-certification-agencies>