

111-85319

Article Number: 111-85319

Description: Identification Tie, 15.4" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg



Base Data	
Local Order Number	IT50L9C2
Type	IT50L
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Identification plate feature allows bundles to be easily marked and identified. • Wire and cable harnesses can be secured and identified using just one product, which saves time. • Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.
Quantity Per	bag
Product Description	HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.
Short Description	Identification Tie, 15.4" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	15.4"
Length L (Metric)	390.0mm
Fixation Method	None
Identification Plate Position	attached to bundle
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	2.2"
Width W (Metric)	56.0mm
Width W2 (Imperial)	0.19"
Width W2 (Metric)	4.7mm
Height H (Imperial)	0.5"

111-85319



Product Dimensions	Height H (Metric)	12.8mm
	Height of printable area (metric)	12.8mm
	Bundle Diameter Min. (Imperial)	0.75"
	Bundle Diameter Min. (Metric)	19.0mm
	Bundle Diameter Max. (Imperial)	3.9"
	Bundle Diameter Max. (Metric)	100.0mm
	Outside Diameter Min. (Imperial)	0.75"
	Outside Diameter Min. (Metric)	19.00mm
	Outside Diameter Max. (Imperial)	3.94"
	Outside Diameter Max. (Metric)	100.00mm
	Thickness T (Imperial)	0.055"
	Thickness T (Metric)	1.4
	Width of printable area (metric)	56.0mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3368-2-9A
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 746B
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	3kg