### SMD ONE PORT 915 MHz SAW RESONATOR

ASR915E





### > STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	914.85	915.00	915.15	
Tolerance from Fo		KHz		±150		
Insertion Loss		dB	-	1.5	3.0	
Quality Factor	Unloaded		-		45,000	
	50Ω loaded				2,100	
Temperature Stability	Turnover Temperature		°C		39.0	
	Turnover Frequency		KHz		Fo+2.7	
	Freq. Temp. Coefficient		ppm/°C <sup>2</sup>		0.032	
Frequency Aging		ppm/year		±10		
DC Insulation Resistance		MΩ	1.0			
RF Equivalent RLC Model	Motional Resistance R <sub>1</sub>		Ω		28.0	40
	Motional Inductance L <sub>1</sub>		μΗ		46.8	
	Motional Capacitance C <sub>1</sub>		fF		3.0	
	Shunt Capacitance C <sub>0</sub>		pF	1.0	1.3	1.6
Operating temp.		°C	-40°C to +85°C			
Storage temp.		°C	-45°C to +85°C			
Max. Rating	DC voltage V		±10			
RF Power Dissipation		dBm	0			

Data measured with: Source Impedance: Zs= $50\Omega$ , Load Impedance: ZL= $50\Omega$ , TA= $25^{\circ}$ C Electrostatic Sensitive Device. Handle with precaution.

### > MARKING:

- 915R - A ZYX (915 Frequency in MHz) (ZY: Date code Z for month from A to L; Y for year,


I.e. 4 for 2004

X: Traceability code)


PIN NO.	CONNECTIONS
1	Input GND
2	Input
5	Output GND
6	Output
3,7	To be GNDed
4,8	Case GND

# 

## > TEST CIRCUIT:



### > OUTLINE DRAWING:



**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



