

Cat5e KVM Console Extender Kit

MODEL NUMBER: **B013-330**



Highlights

- Manage a PS/2 or USB computer/KVM switch from a remote location up to 330ft (100m) away
- Use readily available Cat5e cable for interconnection

Package Includes

- Transmitter and Receiver Unit (1 each)
- 3-ft. PC/KVM Cable Kit (1)
- Power Adapter (DC9V, 1A) for Receiver Unit (1)
- 4-ft. USB A-B Cable (1)
- Quick Start Guide

Description

Tripp Lite's B013-330 Cat5e KVM Extender Kit utilizes Cat5 cabling to extend your computer's Keyboard, Monitor, and Mouse control up to 100 meters (330 ft.) away. The Cat5 KVM Extender Set comprises two units - the Transmitter (Local Unit) and the Receiver (Remote Unit). The Transmitter Unit contains local console ports, allowing the user to have both a local and remote console. The Receiver Unit contains Gain and Equalization knobs that allow the user to manually adjust the video parameters of the remote console. Users can easily optimize the video screen output via these mechanical knobs.

Features

- Enables you to control a PS/2 or USB computer/KVM switch from a distance of up to 330ft (100m) away.
- Can control the computer or KVM switch via both Local and Remote Consoles.
- The remote connection is made using standard Cat5e cable
- Display mode of 1600 x 1200 @ 60Hz
- Shielded Cat5e cables provide better transmission integrity

Specifications

| OVERVIEW | |
|---------------------------------|--------------------------------|
| Accessories Type | Extender Kit |
| PRODUCT OVERVIEW | |
| Product Overview | Cat5e KVM Console Extender Kit |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 6.9 x 8 x 5.5 |
| Shipping Dimensions (hwd / cm) | 17.526 x 20.32 x 13.97 |
| Shipping Weight (lbs.) | 2.04 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|---|-------------------------|
| Shipping Weight (kg) | 0.93 |
| Color | Silver |
| Transmitter Unit Height (in.) | 1 |
| Transmitter Unit Width (in.) | 5.2 |
| Transmitter Unit Depth (in.) | 2.6 |
| Receiver Unit Height (in.) | 1 |
| Receiver Unit Width (in.) | 5.2 |
| Receiver Unit Depth (in.) | 2.6 |
| CONNECTIONS | |
| PC/Server Connections | PS/2; USB; VGA |
| Included KVM Cable (Equipment Side) - Connector 1 | HD15 (Male) |
| Included KVM Cable (Equipment Side) - Connector 2 | (x2) MiniDIN6 (Male) |
| Included KVM Cable (Equipment Side) - Connector 3 | USB A (Male) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>