

NOTE:

- ① MATERIAL, HOUSING: GLASS FILLED 66NYLON (UL 94V-0) BLACK. CONTACT: PHOSPHOR-BRONZE
- ② FINISH: CONTACT, 0.3μ MIN. AU AT CONTACT AREA, 1μ MIN. TIN LEAD AT TINE, OVER NI
- ③ BOSS FOR POSITIONING: P/N -1, -2, -3, -4

注記:


- ① 材料: ハウジング: ガラス入り66ナイロン (UL 94V-0) 色、黒。コンタクト: 黄銅。表面仕上げ: 金メッキ
- ② 表面仕上げ: 金メッキ (全面1.3μ以上のニッケル下地メッキに接触部0.3μ以上の金メッキ, 脚部1μ以上の半田メッキ)
- ③ ボスは型番-1, -2, -3, -4のみ

Pos.	a	A	b	B	c	C	D	E	F	G	H	J	P/N
180	39	49.53	49	62.23	49	62.23	115.57	51.53	64.23	117.57	20.66	28.19	25.54
160	29	36.83	49	62.23	49	62.23	102.87	38.83	64.23	104.87	107.98	15.49	12.84
140	29	36.83	39	49.53	49	49.53	90.17	38.83	51.53	92.17	95.26	102.79	100.14
120	19	24.13	39	49.53	49	49.53	77.47	26.13	51.53	79.47	82.56	90.09	87.44
100	—	—	—	—	49	62.23	—	—	—	64.23	67.32	74.85	72.2
80	—	—	—	—	39	49.53	—	—	—	51.53	54.62	62.15	59.5
60	—	—	—	—	29	36.83	—	—	—	38.83	41.92	49.45	46.8
40	—	—	—	—	19	24.13	—	—	—	26.13	29.22	36.75	34.1

AMP			
AMP (JAPAN), LTD. Tokyo, Japan			
WIRE RANGE	INSULATION DIA	NAME	AMP FH リセクタブルコネクタ (縦直型)
MATERIAL	FINISH	GENERAL TOLERANCE	AMP FH CONNECTOR RECEPTACLE (VERTICAL)
A REVISED (7/1/60)	S. I. Y. FUJII	SIZE	A3 J
O RELEASED J-12583	S. I. Y. FUJII	LOC	J
LTR	REVISION RECORD	SCALE	NOT SCALE
		REV.	A
		SHEET	1 OF 1
		NUMBER	C-176376

CUSTOMER DRAWING

NUMBER C-176376



METRIC

FIG. 191

DIMENSIONS IN MILLIMETERS. DO NOT SCALE PRINT

PRINT 0151

REV. 10/65