

151-31202

Article Number: 151-31202



Description: Cable Tie Anchor Mount, .20" Hole Dia, .20" Max Tie Width, PA66, Black, 1000/pkg

| | | |
|--------------------|-------------------------------------|---|
| Base Data | Local Order Number | CTAM20M4 |
| | Type | CTAM2 |
| | Color | Black (BK) |
| | Features and Benefits | <ul style="list-style-type: none"> • 4-way entry allowing the cable tie to secure bundles running parallel or perpendicular. • Secures with a single screw providing quick installation. |
| | Quantity Per | bag |
| | Product Description | HellermannTyton cable tie anchor mounts are designed with a 4-way entry allowing the cable tie to secure bundles running parallel or perpendicular. The mounts are installed quick and easy by securing a single screw. |
| | Short Description | Cable Tie Anchor Mount, .20" Hole Dia, .20" Max Tie Width, PA66, Black, 1000/pkg |
| Product Dimensions | Length L (Imperial) | 0.8" |
| | Length L (Metric) | 20.4mm |
| | Fixation Method | Screw Mounting and Rivet |
| | Width W (Imperial) | 0.4" |
| | Width W (Metric) | 10.2mm |
| | Cable Tie Width Max. (Imperial) | 0.2" |
| | Cable Tie Width Max. (Metric) | 5.0mm |
| | Height H (Imperial) | 0.2" |
| | Height H (Metric) | 5.1mm |
| | Height H2 (Imperial) | 0.05" |
| | Height H2 (Metric) | 1.78mm |
| | Mounting Hole Diameter D (Imperial) | 0.2" |
| | Mounting Hole Diameter D (Metric) | 5.2 mm |

151-31202



| | | |
|-----------------------------|-------------------------------|----------------------------------|
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | Flammability | UL 94 V2 |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 1000 |
| | Package Quantity (Metric) | 1000 |
| | Customs Number(Schedule B) | 3926909987 |