

170-03175



Article Number: 170-03175

Description: Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel

Base Data	Local Order Number	170-03175
	Type	BSHTTST38SR
	Color	Silver (SR)
	Features and Benefits	<ul style="list-style-type: none"> • A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application.
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		30.48m
Reel Length (imperial)		100.0ft
Bundle Diameter Max. (Imperial)		0.437"
Bundle Diameter Max. (Metric)		11.1mm
Diameter D (imperial)		0.38"
Diameter D (metric)		9.7mm
Nominal Diameter (Imperial)		3/8"
Nominal Diameter (Metric)		9.7mm
Material and Specifications	Material	Glass Fiber (GF)
	Material Shortcut	GF

170-03175



Material and Specifications	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	3926909987
	Reel Weight (Imperial)	2.25lbs
	Reel Weight (Metric)	1.02kg